

# Examination luminaire

HALUX N50-3 P SX D16011000-00806680



<b>fitted with</b>	1 x LED module - Energy efficiency category A+ Ø 18 cm
<b>illuminancefield @ 50 cm</b>	50 000 lx
<b>illuminance @ 50 cm</b>	> 93
<b>color rendering index (CRI)</b>	4400 K, 3800 K, 3300 K
<b>colour temperatur</b>	electronic converter
<b>work equipment</b>	1.8 m Euro
<b>mains lead</b>	polycarbonate & acrylonitrile butadiene styrene copolymer (PC & ABS)
<b>luminaire body</b>	1.3 kg
<b>weight (net)</b>	18 W
<b>Power consumption</b>	keypad at luminaire head
<b>usage</b>	friction
<b>balance of articulation joints</b>	II
<b>class of protection</b>	roll support, rail fastening with removal protection, table clamp with removal protection, universal fastening with removal protection, extension arm with removal protection, wall bracket with removal protection
<b>Accessory</b>	EN 60601-1, EN 60601-2-41
<b>norms</b>	3 color shades, 5 dimming levels, maintenance free
<b>special features</b>	Fastening pin (Ø 16mm)
<b>Fastening</b>	D16011000 - pure white
<b>order number</b>	

## light distribution

