

# Treatment luminaire

TRIANGO 80-1 W D16136000-00808986



<b>Illuminancefield @ 100 cm</b>	Ø 18 cm
<b>illuminance @ 100 cm</b>	Ø 80 000 lx (with dimming 32 000 lx to 80 000 lx)
<b>color rendering index (CRI)</b>	> 95
<b>colour temperatur</b>	4500 K
<b>Depth of illumination L1+L2</b>	1.24 m
<b>work equipment</b>	electronic converter
<b>mains lead</b>	direct power supply
<b>luminaire body</b>	polycarbonate & acrylonitrile butadiene styrene copolymer (PC & ABS)
<b>weight (net)</b>	13.5 kg
<b>Power consumption</b>	30 W
<b>usage</b>	rotary switch on the luminaire head single-pole secondary, continuously dimmable
<b>balance of articulation joints</b>	spring (weight compensation)
<b>class of protection</b>	I
<b>Accessory</b>	sterilizable handle, adapter for suspended ceiling
<b>norms</b>	EN 60601-1, EN 60601-2-41
<b>special features</b>	sterilisable grip, continuously dimmable, maintenance free
<b>Fastening</b>	wall mount
<b>System of protection</b>	IP 20 (43)
<b>order number</b>	D16136000 - pure white

## light distribution

